

Technical Data Sheet

Multi-Tack

Water based Flooring & Construction Adhesive

General purpose Construction Adhesive

Description:

Adheseal Multi-Tack is a specifically formulated acrylic adhesive for bonding timber, plasterboard, metal, concrete F.C. Sheeting and most other common construction materials. The adhesive will provide a strong bond and allows some degree of flexibility for movement. Especially in flooring and wall systems.

Multi-tack is an excellent cornice adhesive.

Multi-Tack is especially suitable for attaching most types of timber to studs and joists. Multi-Tack can also be used to eliminate squeaking of floors by applying to the groove of one sheet prior to the positioning of the next sheet. It can also be used in sub floor construction to assist in preventing warping and squeaks as the timber dries.

Multi-Tack is an excellent adhesive for installation of wall sheeting, mouldings internal and external and can be used to bond polystyrene foam components.

Multi-Tack will adhere to damp surfaces. Do not use where surfaces are saturated with water.

Advantages:

- Highly resilient
- Shock resistant
- Non Sag (anti drip overhead)
- Paintable
- Flexible
- Water clean up
 - Adheres to most surfaces

Application:

1. Ensure surfaces are clean, dry and free of dirt.
2. Sand any warped or twisted timber to attain flush surfaces.
3. Apply a 8-10mm bead of adhesive to floor joists or wall studs. Where panels butt apply two beads approximately 25mm apart. Lay the sheets into position with the least movement possible over the wet adhesive. When installing T&G flooring, apply adhesive to the groove before placement will improve the rigidity of the tongue and groove. Fasten the panel as per the fixing instructions of the flooring manufacturer.
4. Wipe off excess adhesive squeezed out between sheets before it cures.
5. Clean up tools and equipment with water before the adhesive cures.

Properties:

Complies with the following specifications:

A.S. 2753 (fixing plasterboard wallboards)

A.S. 2329 (fixing wallboards other than plasterboard)

Colour : White
Appearance : Thick non-sag paste
S. G. : 1.45 approx.
Solids : 80% approx.
Skin Time : 30 minutes approx.

Technical Data Sheet

Multi-Tack

Water based Flooring & Construction Adhesive

General purpose Construction Adhesive

Packaging:

600ml Sausage

Shelf Life:

2 years

Limitations:

Not suitable for lwater immersion.

Cleaning:

Uncured material can be removed using
water

Safety:

This product is not classified as hazardous however skin irritation and sensitisation may occur in sensitive individuals. Please consult M.S.D.S. for this product for further information.

Technical Data Sheet

Multi-Tack

Water based Flooring & Construction Adhesive

General purpose Construction Adhesive

Guarantee / Warranty:

We warrant our products to be free of defects and manufactured to rigid quality control specifications. As it is impossible to control the use and application of the products, the company's liability is limited to replacing such quantities of product as are proven to be defective. The company disclaims any claims for repainting or other labour resulting from the use of the product. No responsibility is assumed for consequential damages arising from the use of the product. All other warranties including (merchantability or fitness for a particular purpose) are excluded. No representative of the company is authorised to grant any warranty or waive this limitation of liability. All claims concerning product defects must be made within twelve months of shipment. Absence of such claim in writing during this period will constitute a waiver of all such claims with respect to such product.

Adequate Tests: The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions contained herein are made without guarantee or representation as to the results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your requirements.