

Adheseal

Technical Data Sheet:

Gap Filla

Acrylic Gap Sealant

DESCRIPTION:

Adheseal Gap Filla is an acrylic sealant specifically formulated for applications where more rigid fillers crack and /or may fall out.

TYPICAL USES:

Joint sealer for window and door frames, cornices, plasterboard, sidings, vents, tiles etc..

Gap Filla has good adhesion to: Glass, Ceramic, Wood, Brick, Metal, Concrete and many other substrates.

PAINTABLE

WATER CLEAN UP

FLEXIBLE

ADHERES TO MOST SURFACES

PROPERTIES:

Product Type	Acrylic Polymer
Colour	White
Specific gravity	1.50
Dynamic Movement	5% +/-
Tack Free (@25oC)	15 - 20 min
Cure Time @25oC	24 - 48 Hrs

LIMITATIONS:

Adheseal Gap Filla is not recommended for water immersion of for use in chemical environments. It is also not suitable for food contact or high temperature applications. (i.e. Stoves, Fireplaces etc.)

SAFETY:

Eye protection is recommended. In case of contact flush with water for 15 minutes; If irritation persists seek medical attention.

Remove contact lenses before use
Do not handle lenses until all traces are removed from hands and nails.
Keep out of the reach of children.

Adheseal

PACKAGING:

300ml cartridges 20 per carton
Store above 0oC and below 32oC

SHELF LIFE:

Minimum 12 months

GUARANTEE/WARRANTY:

We warrant our product to be free of defects and manufactured to rigid quality control specifications. As it is impossible to control the use and application of the products, the company's liability is limited to the replacement of such quantities of product as are proven to be defective. The company disclaims any claims

for repainting or other labour resulting from the use of the product. No responsibility is assumed for consequential damages arising from the use of the product. All other warranties including (merchantability or fitness for purpose are excluded. No representative is authorised to grant any warranty or waive this limitation of liability. All claims concerning must be made within twelve (12) months of shipment. Absence of such claim in writing during this period will constitute a waiver of all claims with respect to such product.

Adequate Tests: The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions contained herein are made without guarantee or representation as to the results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all your requirements.

Adheseal

PO Box 3113

Stafford DC Qld 4053

A.C.N. 010 441 013

Ph (07) 3356 0000 Fax (07) 3356 0005